

DRIVEWAYS, SINGLE FAMILY (RS) SPECIAL PROVISIONS

In addition to the attached General Provision (TR-0045), the following special provisions are applicable:

I. RURAL LOCATIONS

1. The driveway shall be surfaced with a minimum of 3" (76 mm) of asphalt concrete placed on 6" (152 mm) of well graded and compacted aggregate base and shall conform to the existing pavement.
2. Existing drainage shall not be impaired. Either a valley gutter or a culvert shall be provided.
3. Where a culvert is installed, it shall be installed in the flowline of the existing drainage ditch at a slope to provide maximum drainage.
4. A standard tapered end section shall be installed at the inlet and outlet of the culvert.
5. Any change in the existing drainage pattern, whether occasioned by increase or diversion, and the cost of any damage, repair or restoration of the State highway right of way shall be the responsibility of the permittee.
6. Driveway installation shall conform to the attached plan, "Standard Private and Commercial Road approach in Rural Areas with unimproved Frontage in Conventional State Highway".

II. URBAN LOCATIONS

1. Where curbs exist, the driveway structural section shall be a minimum of 4" (102 mm) of Portland Cement Concrete (PCC) over 6" (152 mm) of aggregate base.
2. Driveway details shall comply with State standards unless local standards exceed the State's.
3. Any existing utility boxes must be either relocated or adjusted to grade at the permittee's expense.
4. Removal of PCC Sidewalks or Curbs: sidewalks or curbs shall be saw cut to the nearest score marks and replaced equal in dimension to that removed with score marks matching existing adjacent sidewalk or curb.